



**FENOPLAST®**

Fügetechnik GmbH

Kundennähe und Flexibilität ist unsere Devise

## FENOSOL® Fittings-Spray

Item no: 200803, 200804



Production information

### Description

FENOSOL® Fittings-Spray – Special maintenance agent for fittings of windows, doors, gates and garages.

FENOSOL® Fittings-Spray contains special additives which ensure easy movement of fittings and reduce wear of the parts.

The spray does not run off, therefore it loosens stuck mechanisms safely and quickly. In addition, it has an anti-corrosive effect, it does not resinify and is resistant to seawater.

With all of the special features it ensures the functionality and durability of fittings.



FENOPLAST Fügetechnik GmbH  
Zur Dornheck 21-23  
35764 Sinn-Fleisbach  
Germany  
Accessed: 03.06.2019

Tel.: +49(0)2772 57587-0  
Fax: +49(0)2772 57587-20  
Email: [info@fenoplast.de](mailto:info@fenoplast.de)  
[www.fenoplast.de](http://www.fenoplast.de)  
Effective 06/2019





**FENOPLAST®**

Fügetechnik GmbH

Kundennähe und Flexibilität ist unsere Devise

## Application areas

FENOSOL® Fittings-Spray is specifically designed for the maintenance of fittings on windows, doors and gates. It can also be used on mechanisms where permanent internal and external lubrication is necessary.

## Application

Spray the fittings of windows, doors, gates and garages from a short distance. 1 to 3 pumps are sufficient. No after-treatment necessary. We recommend biannual maintenance.

## Technical specifications

|                                |   |          |
|--------------------------------|---|----------|
| Chemical base                  | Preparation of synthetic oils and additives in environmentally neutral propellant gas |          |
| Colour                         | brownish  |          |
| Density                        | approx. 0,605 g/cm <sup>3</sup>   | at 20 °C |
| Flashpoint                     | < -20 °C  |          |
| Minimum processing temperature | 0 °C  |          |

Product information

2



FENOPLAST Fügetechnik GmbH  
Zur Dornheck 21-23  
35764 Sinn-Fleisbach  
Germany  
Accessed: 03.06.2019

Tel.: +49(0)2772 57587-0  
Fax: +49(0)2772 57587-20  
Email: [info@fenoplast.de](mailto:info@fenoplast.de)  
[www.fenoplast.de](http://www.fenoplast.de)  
Effective 06/2019



**FENOPLAST®**

Fügetechnik GmbH

Kundennähe und Flexibilität ist unsere Devise

## Delivery form

Item no. 200803: 100 ml sprayer, 1 PU = 12 sprayer cans in a box

Item no. 200804: 500 ml sprayer, 1 PU = 12 sprayer cans in a box

## Storage

Store in cool and dry place. Keep away from direct sunlight. Keep away from children.

Storage temperature: 5 °C to 25 °C.

Production information

3

**Please refer to the safety data sheet for safety-relevant data!**

NOTE: The above information can only be used as a general guide. The listed features and performance characteristics are approximate values, which are not part of the product specification. Because of the processing and application conditions outside of our influence and the multitude of different materials, we recommend to carry out sufficient self-tests. A liability for specific application results can therefore not be derived from the information and notes in this leaflet. In the context of our sales conditions, a guarantee is given solely for the consistently high quality of our products. With the publication of this edition, all previous technical information sheets are invalid.



FENOPLAST Fügetechnik GmbH  
Zur Dornheck 21-23  
35764 Sinn-Fleisbach  
Germany  
Accessed: 03.06.2019

Tel.: +49(0)2772 57587-0  
Fax: +49(0)2772 57587-20  
Email: [info@fenoplast.de](mailto:info@fenoplast.de)  
[www.fenoplast.de](http://www.fenoplast.de)  
Effective 06/2019

